




Status of the JSNS²-I / II

ChangDong Shin (KEK)
On behalf of the JSNS² I / II collaboration


JSNS² / JSNS²-II Collaboration

(J-PARC Sterile Neutrino Search at J-PARC Spallation Neutron Source)

Collaboration meeting @ J-PARC (2020/Feb)




- JSNS² collaboration (61 collaborators)
- 10 Korean institutions (24 members)
 - 6 Japanese institutions (29 members)
 - 4 US institutions (7 members)
 - 1 UK institution (1 member)



JAEA
KEK
Kitasato
Kyoto
Osaka
Tohoku



Chonnam National
Jeonbuk National
Dongshin
GIST
Kyungbook
Kyung Hee
Seoyeong
Soongsil
Sungkyunkwan
Seoul National of
sci and tech



BNL
Florida
Michigan
Utah



Sussex





Indication of a sterile neutrino ($\Delta m^2 \sim 1 eV^2$)

- Anomalies, which cannot be explained by standard neutrino oscillations for ~ 20 years are shown

Experiments	Neutrino source	Signal	Significance	E(MeV)	L(m)
LSND	μ Decay-At-Rest	$\bar{\nu}_\mu \rightarrow \bar{\nu}_e$	3.8σ	40	30
MiniBooNE	π Decay-In-Flight	$\nu_\mu \rightarrow \nu_e$	4.8σ	800	600
		$\bar{\nu}_\mu \rightarrow \bar{\nu}_e$			
BEST	e capture	$\nu_e \rightarrow \nu_x$	4.2σ	<3	10
Reactors	Beta decay	$\bar{\nu}_e \rightarrow \bar{\nu}_x$	3.0σ	3	10-100

- JSNS² uses the same neutrino source (μ), target (H), and detection principle (IBD) as the **LSND**
 - Even if the excess is not due to the oscillation, JSNS² can catch this directly
 - two advantages : short-pulsed beam and used the gadolinium(Gd)-loaded liquid scintillator(GdLS)

J-PARC facility




Low duty factor beam
(short-pulses + low repetition rate)
Gives an excellent signal to noise ratio

1 MW (design)

- 0.6MW (2021 Jan - Apr/5)
- 0.7MW (2021 Apr/5 - June/22)
- 0.7MW (2022 Jan/28 - Apr/6)
- 0.8MW (2022 Apr/7 - Jun/3)
- 0.8MW (2023 Apr/15 - Jun/2)

JSNS² detector




	Liquid	Volume
Target	GdLS + DIN (10%)	17 tons
gamma-catcher and veto	Pure LS	31 tons

- 96, 10-inch PMTs for the inner detector
- 24, 10 inch PMTs for the veto

Production and detection

- If sterile ν exist, $\bar{\nu}_\mu \rightarrow \bar{\nu}_e$ oscillation occurs with **24m**.
- Coincidence of Inverse Beta Decay (IBD)
 - Positron annihilation
 - Neutron capture on Gd




	Timing	Energy
Prompt	$1.5 < T_p < 10 \mu\text{s}$	$20 < E < 60 \text{ MeV}$
Delayed	$\Delta T_{p-d} < 100 \mu\text{s}$	$7 < E < 12 \text{ MeV}$



Expected energy spectrum and sensitivity


- $\bar{\nu}_e$ follows decay-at-rest $\bar{\nu}_\mu$ energy distribution
- Prompt single rate: $\sim 3.9 \times 10^{-4}$ per spill
- Delayed single rate: $\sim 4.8 \times 10^{-3}$ per spill
- Spectral fit is sensitive to the difference of energy spectrum

Signal	$\sin^2 2\theta = 3.0 \times 10^{-3}$ $\Delta m^2 = 2.5 eV^2$ (Best fit values of MLF)	87
	$\sin^2 2\theta = 3.0 \times 10^{-3}$ $\Delta m^2 = 1.2 eV^2$ (Best fit values of LSND)	62
background	$\bar{\nu}_e$ from μ^-	43
	$^{12}\text{C}(\nu_e, e^-)^{12}\text{N}_{g.s.}$	3
	beam-associated fast n	≤ 2
	Cosmic-induced fast n	negligible
	Total accidental events	20



Operation




- Now beam power is very close to the design (1MW).
- 0.95MW at RCS
- There is an accelerator maintenance period every year.
- 3.28×10^{22} POT has been delivered. (28.7% of the approved POT of JSNS²)



Commissioning run

(Eur. Phys. J.C (2022) 82:331)

- Integrated POT : 8.9×10^{20}
 - expected IBD $\ll 1$ event
- Beam trigger with $25\mu\text{s}$ width





Observed correlated event candidates

- 59 ± 8 events / 8M spills
- Cosmic-induced fast neutrons are the dominant background
 - expected cosmic-induced fast neutron is 55.9 ± 4.3 events
 - Pulse shape discrimination (PSD) would reject them.


Pulse Shape Discrimination (PSD)

- Fast neutrons can mimic IBD signals from electron anti-neutrino.
 - correlated background
- PSD can separate the IBD signals and fast neutrons.
 - the goal is to remove 99% of fast neutrons.





The conventional PSD method

- The conventional PSD method uses the charge of the tail (Q_{tail}) and total region (Q_{total}) in the waveform.
- Generally, neutrons have large $Q_{\text{tail}}/Q_{\text{total}}$ compared to leptons.





^{252}Cf source with a 10inch PMT



Likelihood method


- The DAQ of JSNS² can measure a waveform every 2ns (500MHz sampling).
- The likelihood judges that all other points look like “neutron” or “electron” after peak normalization as 1.



2-Dimensional likelihood method

- More improvement of PSD capability is needed to get better sensitivity for sterile neutrino search.
- There are two types of waveforms in the ME control sample.
 - 2 dimensional likelihood is developed to separate them

average waveform





- The after-pulse from the parent muon affects the waveform of the following ME event.

PSD results with 2D likelihood method





- The ME efficiency with 95% of the FN rejection is 90.98 +/- 0.05%.
- Both ME efficiency and FN rejection depend on a reference point.

FN rejection vs ME efficiency




Convolutional Neural Network (CNN)

- Treated time-series data from a PMT with image data.
- Two independent efforts show consistent FN rejection results.



Cosmic muon identification




- Michel electron induced by cosmic muon and muon itself are one of backgrounds.
- Cosmic muon can be tagged by Top/Bottom Veto PMTs.
 - 12 PMTs on Top
 - 12 PMTs on Bottom
- Stopping muon candidates rate : 1487.8 ± 0.5 Hz
- Through-going muon candidates rate : 605.4 ± 0.4 Hz
- Michel candidates rate : 110.1 ± 0.2 Hz (10~60 MeV)

Single rates of the prompt and delayed


- 125 μs time window from beam timing.
- External particles and the ME are rejected.

	Prompt	Delayed
Single rate	$(2.20 \pm 0.09) \times 10^{-4}/\text{spill}$	$(1.80 \pm 0.01) \times 10^{-2}/\text{spill}$

IBD prompt candidate energy spectrum





IBD delayed candidate energy spectrum



KDAR neutrino measurement

Kaon Decay-At-Rest neutrino measurement (KDAR neutrino: 236 MeV mono-energetic)

- Neutrino interaction models are a crucial part of neutrino physics, but poorly known at low energies.
- **The JSNS² detector has the unique ability to measure the mono-energetic KDAR neutrino.**
- Note that it is hard to see a clear energy peak of KDAR neutrinos in the data of the horn focused beam.




KDAR signal measurement in JSNS²

A double coincidence between

- The initial neutrino interaction products and the subsequent muon decay.


Hg target

KDAR




Detector

Prompt





Delayed




KDAR Event Signature

JSNS² Detector



KDAR Timing Signature




First clear KDAR signal

(Toward first precise KDAR measurement)

- KDAR peak is clearly seen
- High purity (95%) KDAR signal
 - Background: 5.2 %
- Note that **the systematics on the energy scale are not included yet.**


BKG ID	Correlated/ Accidental	BKG (# of events)	
1	Correlated	36.6 +- 34.8	5.0 +- 5.1%
2	Accidental	1.5 +- 0.1	0.2 +- 0.01%
KDAR Candidates : 730 events		38.1 +- 38.4	5.2 +- 5.3%



JSNS²-II


JSNS²-II (Second phase of JSNS²)

- New far detector
 - fiducial 32 tonnes and 48 m location
- Two detectors with two different baseline
 - a solid conclusion on LSND anomaly
- The construction is being progressed rapidly.





New far detector

- Almost identical to the existing near detector
 - 37m³ Gd-LS for the neutrino target
 - 150m³ no Gd-loaded LS for the veto and gamma catcher.
 - 228 PMTs will be used
- The detector is placed outside of building
→ Electronics in the “roof space”



Sensitivity of JSNS²-II

- Each background simulation was done based on the JSNS² data.
- The sensitivity becomes better in the low Δm^2 region.





Construction of Stainless Steel Tanks

- The stainless steel tanks has been constructed.
- The S.S tank was placed at east side of the MLF building.




Acrylic Tank

- Acrylic tank for the detector target was made by Taiwan company.
- The transmittance of the acrylic well covers the wavelength region of scintillation light.
→ ~93% @ 400~600nm
- The acrylic tank will be installed to the inner S.S tank.



PMT preparation

- 190 PMTs were donated from Double-Chooz
- Dead PMT check was done.
- Our jigs for the far detector were assembled.




PMT installation

- 142 PMTs were installed.
 - barrel and top lid of the inner detector
- Bottom PMTs will be installed soon
- Calibration system was installed
 - LED
 - temperature sensors




Construction schedule of JSNS²-II



Summary

- There have been 1st (2021), 2nd (2022) and 3rd (2023) long physics runs in JSNS².
- Analyses are ongoing with the data.
 - Has been developing PSD tools
 - Single rates in both prompt and delayed time window were measured
 - Background study is ongoing
- JSNS² is working toward the first precise KDAR measurement.
 - clearly see the high purity KDAR signal
- The JSNS²-II detector is under construction.
 - first data taking on next year

Thank you for your attention



acknowledgements:

- MEXT, JSPS (Japan)
- Korea Ministry of Science, NRF (Korea)
- DOE, Heising-Simons Foundation (US)
- Royal Society (UK)

